



**SILVERBACK®**  
VAPOR BARRIER

**20 MIL SILVERBACK® (SR)**  
*Cord Reinforced Vapor Barrier*



## FEATURES

- Clean white facing and silver back
- Made from 100% virgin polyethylene
- No welded seams = ONE FULL PIECE
- Easy installation
- 30% thicker than nearest competitor
- 30 year warranty
- Crawl Space Encapsulation® Approved
- Lab tested for VOCs, odors and off-gassing



## AVAILABLE SIZES:

6'9" X 100' – 675 ft<sup>2</sup> (20MSB-100)  
13'4" X 50' – 675 ft<sup>2</sup> (20MSB-50)  
13'4" X 75' – 1000 ft<sup>2</sup> (20MSB-75)

THICKNESS (STRING)	Nominal 26 mil (0.66 mm) ±
THICKNESS (PLASTIC)	Nominal 22 mil (.56 mm) ± 10%
WEIGHT	110 lbf/msf
CONSTRUCTION	Extrusion Laminated with Scrim Reinforcement
GRAB TENSILE	140 lbf
ELONGATION @ SCRIM BREAK	18%
TRAPEZOID TEAR	98 lbf
CBR PUNCTURE RESISTANCE	335 lbf
PERM RATING	0.022 grains/(ft <sup>2</sup> •hr•in Hg)
MAXIMUM STATIC USE TEMP	180° F (82° C)
MINIMUM STATIC USE TEMP	-70° F (-57° C)



### LIMITED LIFETIME WARRANTY

SilverBack® warrants that their products will be free from material defects and workmanship, under normal proper use, storage and operating conditions for thirty years.

For full warranty information, visit [CrawlSpaceEncapsulation.com](http://CrawlSpaceEncapsulation.com)

**VISIT SILVERBACKVAPORBARRIER.COM FOR MORE**